

### Flexibility and Value

- FLEXIBILITY**  
Be prepared for present and future needs with patented PowerSnap technology
- DURABILITY**  
Meets or exceeds industry standards
- DESIGN**  
Save time and money while improving customer service levels

PowerPedestal.com 918.341.6811 ■ sales@powerpedestal.com

## Proven Capabilities. Maximum Capacity.

- Centrally located to maximize your shipping effectiveness
- ISO 9001:2008 certified
- Advanced fusing technology with McElroy Fusion
- Ferry Modified 6000: The largest bi-axial rotomold machine
- State-of-the-art PLC leak detection system

rotomoldusa.com

800.825.3379 • Fax: 918.343.1390 • roteksales@rotomoldusa.com

## HydroLocker® Innovative Dock Storage

HydroLocker® is the most attractive dock locker on the market! Vandal-resistant hinges with internal fittings for added security to store your valuables. Constructed with UV-stabilized polyethylene making it corrosion and impact resistant. It provides a generous 11.5 cubic feet of clean dry storage and can double as a mounting stand for the EnergyMate®.



PUSH BUTTON CONTROL



HYDROLAUNCH™ CONTROL PANEL

## Control Upgrades

The **Push Button control** uses automatic valves, eliminating the need for handles and levers. One button to lift, one to lower, and one to stop makes using your boat lift effortless. The **HydroLaunch™ Remote Control** is capable of operating most brands of hypopneumatic style boat lifts which are intended to be controlled with one air valve.



**HydroHoist® Marine Group Corporate Office**  
915 West Blue Starr Drive | Claremore, OK 74017 USA  
**918-341-6811** (U.S.) | **001-918-341-6811** (International)  
boatlift.com | sales1@boatlift.com



B2BB017 | © 2017 HYDROHOIST MARINE GROUP | 11-16

**Authorized HydroHoist® Dealers are located throughout North America, Europe and the Pacific.**

For the name of the dealer servicing your area, phone 918-341-6811 in the U.S., or visit our Web site at boatlift.com.

**MISSOURI DISTRIBUTION CENTER**  
4065 East US Hwy. 54  
Linn Creek, MO 65052  
573-346-7505

**OKLAHOMA DISTRIBUTION CENTER**  
453265 E. Hwy 85-A  
Bernice, OK 74331  
918-256-8125

**TENNESSEE DISTRIBUTION CENTER**  
1825 Gainesboro Hwy.  
Baxter, TN 38544  
931-372-8928

**TEXAS DISTRIBUTION CENTER**  
83998 N. State Hwy 289  
Pottsboro, TX 75076  
903-786-5438



MARKET ORIGINATOR.  
INDUSTRY INNOVATOR.



918.341.6811 | boatlift.com | hydrohoist.com



We didn't set out to become the  
**world's premier boat lift manufacturer.**

We were simply looking for a practical solution for keeping boats clean and dry when not in use — without having to transport them inland — a solution that would enable anyone to launch or dry-dock the boat with minimal effort.

**HydroHoist®** boat lifts have evolved from a simple idea into a sophisticated, yet user-friendly, method of total boat care that is embraced worldwide. Using state of the art designing software and 3D modeling, each lift is professionally engineered and designed for its application.

**HyPower™** provides a line of easy-to-maintain power pedestals suited for marina and RV applications with the patented PowerSnap® panels and weather bases paired with the EnergyMate® and PowerPort® pedestals.

Centrally located in Oklahoma, **RotoMoldUSA** provides superior rotomolding services — including the industry-known blue tanks for HydroHoist boat lifts, and additionally provide services to several Fortune 100 companies ranging from pharmaceutical to agriculture to transportation. Featuring equipment such as the McElroy Fusion and Ferry 280, RotoMoldUSA's design and engineering assistance maximizes the benefits of rotational molding.





## UltraLift2™ 4,400 – 32,000 Series

### STANDARD FEATURES

- Precision-designed, custom-molded, high-impact polyethylene tanks
- All cast parts are (HSLA) High-Strength Low Alloy steel making them 40 percent stronger than fabricated steel
- Heavy-duty construction with Hot-dipped, zinc-galvanized structural steel frame/fasteners
- Grade-8 pivot hardware with two-piece stainless/ polyethylene pitman bushings
- Heavy-duty 0.25" (0.0635 cm) thick torsion bars
- 5" (12.7cm) high-density polyethylene square-hole bushings
- Heavy-duty structural-grade dock brackets with molded bumper guards (HydroGuard™)
- All steel parts are above the water\*

### RECOMMENDED FOR

- Boat up to 32,000 lbs./14,500 kg and up to 50'/15.25m overall length
- V-hull, Pontoon, Tritoon or Sailboat
- Inboard or stern drive
- Drive-in or back-in installations
- Floating docks with U-shaped slips

\*Exceptions may be necessary for proper installation.



High impact polyethylene tanks

All steel parts are above the water\*

Lifts boats up to 32,000 lbs. (14,500 kg) and 50 ft. (15.25m) overall length



## ULTRALIFT2™ SERIES BOAT LIFTS

## HarborHoist™ Boat Lift

The **HarborHoist™** has a level-lifting frame constructed of aircraft-grade aluminum and is HydroHoist's most versatile lift yet — perfect for fresh and salt water.

### STANDARD FEATURES

- Most versatile, free-floating lift
- Rugged, marine-grade polyethylene tanks
- Aluminum structure to extend the life of the product
- Easy loading and unloading of passengers
- Controls integrated with lift
- Simple assembly and installation

### RECOMMENDED FOR

- Boats up to 12,000 lbs./5,400 kg
- Inboard, Wake, Pontoon, Tritoon boats
- Fixed or floating U-shaped single- or double-wide slips, L-shaped and square docks
- All water types including brackish and salt



## HarborHoist™



## HydroPort™ Series PWC Docking Platform

### STANDARD FEATURES

- PWC is fully roller supported
- Easiest load and launch of any PWC docking platform
- Ultra-tough polyethylene construction with Expanded Polystyrene (EPS) Marine Foam — Increased strength and leak elimination
- Flat anti-skid walking surfaces
- CNC molds for exact form, function, and fit
- Fourteen high-performance 5" x 2" rollers
- Exclusive "Air-Pillow" bow stop
- Easily adjustable 5" x 2" rollers to accommodate all models of watercraft
- Stainless steel roller axles for increased strength and compatibility with fresh, brackish, and salt water

### RECOMMENDED FOR

- One-, two- and three-place PWCs
- Load capacity up to 1625 lbs./738 kg
- 12' 6" (3.81 m) length; 4' 10" (1.47 m) width; 15" (38.1 cm) depth
- Floating or fixed docks
- Front- or side-mount mooring hardware



Universal mount for floating or fixed docks



Rigid Mount Hardware for Floating docks. (shown with optional heavy-duty brackets)

ALSO AVAILABLE



Exclusive bow stop to slow your craft's forward motion and provide a soft rest for the keel

In-line rollers make launching your craft easy

Multi-link and side mount capabilities



## Marine Accessories

The **Bow Guide** aligns the boat in the slip while offering protection to the keel. The **Corner Bumpers** offer peace of mind when pulling in to your slip, protecting the boat from contact with the dock. Superior design both in functionality and aesthetics — the Corner Bumper has multiple attachment points and will fit on docks with both internal and external roof posts.



BOW GUIDE



CORNER BUMPER



HYDROFENDER™



ULTRAFENDER™

Providing additional protection is the **HydroFender™** — a high quality dock edge bumper designed to take the place of traditional rub rail. The **UltraFender™** is perfect for transient gas and premium docks.

America's #1 Boat Lift



918.341.6811  
boatlift.com



HydroHoist®  
BOAT LIFTS

